

# TEMPO LE

## Slow Combustion Space Heater.

The **TEMPO LE** was designed by **KEMLAN** as a modern, efficient replacement for the pot belly stove.

The **TEMPO LE** uses the same 115mm (4 1/2") flue as most pot belly stoves and is designed to heat an area up to 140 sq.m. (15 squares).

### ROBUST

- 6 mm welded steel firebox.
- Firebrick lined floor.
- Heavy duty hinges and catches.
- Stainless steel glass holder.

### SIMPLE

- One easy slide control.
- No levers, rods or dampers.
- Easy to light.
- Steady controllable heat.
- Removable heavy baffle plate.

### SAFE

- Rear shielded firebox.
- Ceramic glass door.
- Tested to Australian Standards AS/NZS 2918 for safety clearances. (Refer specifications)
- The **KEMLAN TEMPO LE** freestanding solid fuel appliance complies with the requirements of AS/NZS4013 for emissions.

### EFFICIENT

- Useable cooktop
- Preheated air supply to fire.
- Low emissions.
- High output.
- Combined radiant and convection heater.

### LONGLASTING

- **KEMLAN** is an all Australian company noted for the production of quality products backed by an unsurpassed record of after sales services since 1969. From the outset, the founders built their fireplaces to work and last. The **TEMPO LE** is the result of continuous research and development and maintains the **KEMLAN** tradition.

- **10 YEAR WARRANTY.**



**TEMPO LE NO. 1**  
Pot Belly Replacement (P.B.R.)  
Rear Heat Shield.



**TEMPO LE NO. 3**  
Side Panels  
Double Rear Heat Shield.

**No. 1.**

**SPECIFICATIONS**  
**Tempo LE No. 1**  
**(Pot Belly Replacements)**

- Clearances to combustible materials
- Rear Wall:** 225 mm
- Side Wall:** 575 mm
- Corner Wall:** 350 mm
- Clearance to rear wall as shown is with one 900 mm length of flue shield fitted
- **Hearth:** requirements as below.
- Weight 84 kgs.

---

**No. 3.**

**Tempo LE No. 3**

- Clearance to rear wall as shown is with one 900 mm length of flue shield fitted.
- Without flue shield clearance should be 285mm.
- **Hearth:** Thickness to be a minimum of 14 mm non-combustible material and must extend 300 mm in front of the firebox door and 200 mm to the sides. Minimum Hearth requirements -
- Standard Hearth:** 950 mm x 950 mm.
- Corner Hearth:** 1050 mm x 1050 mm with a 600 mm front edge.
- Weight 92 kgs.

Due to continuing research and development specifications may change without notice.



KEMLAN INDUSTRIES PTY LTD A.B.N. 43 003 209 961  
SPECIALISTS IN FIREPLACE DESIGN & MANUFACTURE  
HEAD OFFICE:  
59 Pirrama Rd., Sydney, N.S.W.  
P.O. Box 259 Zillmere Qld., 4034 Australia  
**Telephone: (07) 3263 6988 Facsimile: (07) 3263 6150**  
www.kemlan.com

**Your Local Retail Outlet:**